

Datasheet

Absen Polaris PL2.5 Pro V2

The Polaris PL2.5 Pro V2 is the successor to the popular Polaris 2.5 Pro LED material. What has changed? It is now even more suitable for the rental market - thanks to a completely new developed frame and all pixels being additionally glued over the entire surface. The result: twice as robust and lighter panels.

LED Type	Black SMD 3in1 1515
Pixel Pitch	2.5 mm
Resolution	200x200
Panel Dimensions (WxHxD)	500x500x78 mm
Panel Weight	7.5 kg
Brightness	1,200 nit
Refresh Rate	3,840 Hz
Gray Scale	16 Bit
Contrast Ratio	5,000:1
Viewing Angle (h/v)	160° / 140°
Operating Temperature	-10~ °C / +40 °C
IP Rating (Front/Rear)	IP40 / IP21
Power Consumption pro Panel	100 % Weiß 135 W, 60 % Content Mix 80 W
Module Maintenance	Vorderseite / Rückseite
Panel Installation Type	Hanging / Stacking
Max. Rigging Quality (vertical)	20 Panel
Curving (convex / concave)	-7.5° bis +10°



✓ The new Definition of Robust

Do you have any questions?
Our sales team is happy to assist you!

✉ vertrieb@niclen.de

☎ +49 231 99961 0